



# VelociWrap™

## General Specifications:

Material:	Virgin Polypropylene Resin
Tensile Strength:	400 lbs (181 kgs)
Mean Diameter:	1/8"
Max Operating Temperature:	180° F (82° C)
Melting/Breakdown Temperature:	320 ° F (160° C)
Spool Length:	11,000' (3,352 m)
Color:	Cherry Red
Packaging:	Single Spool Shrink Wrapped

## Physical Dimensions:

Spool Diameter:	1'-0"
Spool Height:	1'-2"
Spool weight:	28 lbs (13 kgs)

## Pallet Specifications:

Pallet Quantity:	32 Rolls
Length per Pallet:	352,000' (107,290 m)



## VelociWrap™ Features:

- 11,000 ft (3,352 m) length for maximum amount of wrapped cable between loads
- Engineered and manufactured exclusively for VelociWrapper
- Available in single rolls or by the pallet which includes 32 rolls
- Purchased through [VelociWrapper.com](http://VelociWrapper.com) or by calling 1-866-TRIPLEX (874-7539)

## VelociWrap™ Information:

Max applied tension under normal operating conditions:	48 lbs (22 kgs) per strand
Spool quantity to reload VelociWrapper:	3 spools
Estimated trench feet wrapped per load:*	8,250' (2,515 m)
Estimated trench feet wrapped per pallet:*	88,000' (26,822 m)

\* Estimates based on three 1250 kcmil cables

## VelociWrap™ Storage:

Damage may occur to the VelociWrap™ if stored in direct sunlight. Store away from sunlight for maximum lifespan.